

フルHD シリーズ 16:9

23.6型 ワイド



Specifications for ProLite B2409HDS-B: 1920x1080 resolution, 20000:1 contrast, 300cd/m² brightness, 2ms response time. Includes features like Eco buttons, HDMI & DVI-D & D-SUB, and HDCP.

21.5型 ワイド



Specifications for ProLite E2209HDS-B: 1920x1080 resolution, 20000:1 contrast, 300cd/m² brightness, 2ms response time. Includes features like Eco buttons, HDMI & DVI-D & D-SUB, and HDCP.

ワイド シリーズ 16:10



Specifications for ProLite E2607WS-B: 1920x1200 resolution, 4000:1 contrast, 300cd/m² brightness, 2ms response time. Includes features like Eco buttons, HDMI & DVI-D & D-SUB, and HDCP.



Specifications for ProLite B2006WS-B: 20-inch WSXGA+, 2000:1 contrast, 300cd/m² brightness, 5ms response time. Includes features like Eco buttons, HDMI & DVI-D & D-SUB, and HDCP.

※液晶パネルを縦長で使用するときには、soft OSMが必要です。soft OSMは弊社ホームページよりダウンロードできます。



Specifications for ProLite E2205WS-B: 1680x1050 resolution, 1000:1 contrast, 300cd/m² brightness, 5ms response time. Includes features like Eco buttons, HDMI & DVI-D & D-SUB, and HDCP.



Specifications for ProLite E2002WS-B: 1680x1050 resolution, 3000:1 contrast, 300cd/m² brightness, 5ms response time. Includes features like Eco buttons, DVI-D & D-SUB, and HDCP.

スクエア シリーズ

SQUARE



Specifications for ProLite E1902S-B: 1280x1024 resolution, 1000:1 contrast, 300cd/m² brightness, 2ms response time. Includes features like Eco buttons, DVI-D & D-SUB, and HDCP.



Specifications for ProLite E1702S-B: 1280x1024 resolution, 1000:1 contrast, 300cd/m² brightness, 5ms response time. Includes features like Eco buttons, DVI-D & D-SUB, and HDCP.



Specifications for ProLite E3835-B5: 1024x768 resolution, 600:1 contrast, 250cd/m² brightness, 8ms response time. Includes features like Eco buttons, DVI-D & D-SUB, and HDCP.

タッチ シリーズ

TOUCH



Specifications for ProLite T1930SR-B1: 1280x1024 resolution, 800:1 contrast, 240cd/m² brightness, 90° tilt. Includes features like Eco buttons, DVI-D & D-SUB, and 90° tilt stand.

Specifications for ProLite T1730SR-B1: 1280x1024 resolution, 800:1 contrast, 240cd/m² brightness, 90° tilt. Includes features like Eco buttons, DVI-D & D-SUB, and 90° tilt stand.

Specifications for ProLite T1530SR-B1: 1024x768 resolution, 500:1 contrast, 280cd/m² brightness, 90° tilt. Includes features like Eco buttons, DVI-D & D-SUB, and 90° tilt stand.

Table with 7 columns listing monitor models (e.g., PLB2409HDS-W1/B1, PLE2209HDS-W1/B1) and their detailed specifications including resolution, contrast, brightness, response time, and input/output ports.

Table with 4 columns listing monitor models (e.g., PLE1902S-W1/B1, PLE1702S-W2/B2) and their detailed specifications including resolution, contrast, brightness, response time, and input/output ports.

Table with 4 columns listing touch panel models (e.g., ProLite T1930SR-W1/B1, ProLite T1730SR-W1/B1) and their detailed specifications including resolution, contrast, brightness, response time, and input/output ports.

※1 TFT液晶画面は非常に精密度の高い技術で作られていますが、ごくわずかの画素欠けや発熱時点灯する画素がある場合があります。 ※2 表示可能な最大解像度以外の低い解像度では、画面拡大処理をしておりますので、表示される文字がぼやけたり線が部分的に太くなります。 ※3 オーディオ機器未接続時 ※4 液晶パネル及びバックライトは1年保証になります。 ※5 ACR機能 (Advanced Contrast Ratio) ※6 DCR機能 (Dynamic Contrast Ratio) ※7 標準: タッチパネル装着時

お問い合わせはこちら (Contact Us) section with iiyama logo and support center information.

TEL 03-3570-6374 (Telephone) and FAX 03-3570-6375 (Facsimile) contact information.

support@iiyama.jp (Email) and support@iiyama.jp (Website) contact information.

iiyamaリサイクルサービス (iiyama Recycling Service) and TEL 0269-81-2072 (Telephone) contact information.